

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2000-286709

(43)Date of publication of application : 13.10.2000

(51)Int.Cl.

H03M 7/14
G11B 20/14

(21)Application number : 2000-020171

(71)Applicant : VICTOR CO OF JAPAN LTD

(22)Date of filing : 28.01.2000

(72)Inventor : HAYAMIZU ATSUSHI

(30)Priority


Priority number : 11023316 Priority date : 29.01.1999 Priority country : JP

(54) MODULATION METHOD, MODULATION DEVICE, DEMODULATION METHOD,
DEMODULATION DEVICE AND RECORDING MEDIUM

(57)Abstract:

PROBLEM TO BE SOLVED: To improve an encoding rate by permitting a code table to store a code word corresponding to an input data word and state information showing an encoding table used for encoding the next input data word and selecting the plural encoding tables.

SOLUTION: An 8-15 modulator 13 converts the input data word of eight bits, which is inputted through a format part 12, into the code word of 15 bits by referring to a code table 120. An NRZI conversion circuit 14 receives a code word, generates an NRZI signal and records it in a recording medium 2 through a recording medium driving circuit 15. At the time of constituting the code table 120, the code word is allocated based on a limit that a minimum run length is 3T and a maximum run length is 11T with a channel bit as T. The table is divided into seven groups 7 based on a transition state and the group can be selected in accordance with a following input data word. Thus, the run length limit is satisfied even if the code word is directly connected.



BEST AVAILABLE COPY

LEGAL STATUS

[Date of request for examination] 27.09.2002

[Date of sending the examiner's decision of rejection] 13.07.2004

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]